



# Chain link

A WIDE RANGE OF SIZES ARE AVAILABLE WITH A PALLETISED COMPACT WOUND PRESENTATION AND IS SAFE AND QUICK TO HANDLE, OFF LOAD, WITH ACCOMPANYING SAVINGS IN STORAGE AREAS AND TRANSPORT COSTS.

## Benefits

- Standard PVC coatings are green and black – a wide choice of other colours available upon request.
- Choice of Barbed or Knuckled tops and bottoms dependent upon the degree of security requirement.
- The configuration and size of mesh makes it difficult to climb.
- If breached, the intrusion can be readily spotted.
- Ideal for re-class on existing posts.
- Can be strained to produce a 'flat' fence line – even the heaviest of gauges.
- Available throughout the UK from a nation wide network of stockists.

## A wide range of applications

Chain Link has been proven in service over the years to be a strong, durable fencing material, which fulfils many demanding roles. It is essential that the right type, manufactured to specific recognised standards is selected for

an acceptable performance. When chosen correctly, Chain Link will satisfy a wide range of fencing applications from domestic garden boundary to high security and is quicker to erect than most kinds of fences giving a low cost installation.



All rolls come complete with line wires and with knuckled edges. Barbed (protruding) edges increase the security of the fence and are available to order. Barbed edges can be supplied along the top of the fence, along the bottom or both.

Standard Wire Diameters

- Galvanised: 2.50mm  
3.00mm  
3.55mm  
5.00mm
- PVC Coated Bright Core: 2.50/1.70mm  
3.15/2.24mm  
3.55/2.50mm  
4.00/3.00mm
- PVC Coated Galvanised Core: 2.65/1.90mm  
3.15/2.24mm  
3.55/2.50mm  
4.00/3.00mm  
4.75/3.55mm  
6.40/4.70mm
- Jumbo:

- Standard Heights: 900mm  
1200mm  
1400mm  
1800mm  
2400mm  
2750mm  
3600mm

- Standard Mesh Sizes: 50mm  
45mm  
40mm  
25mm

Chain Link is the most versatile of fencing fabrics and most combinations of the above can be manufactured.

**Finish**

All rolls come complete with line wires and with knuckled edges. Barbed (protruding) edges increase the security of the fence and are available to order. Barbed edges can be supplied along the top of the fence, along the bottom or both.

Colour coated black or green  
Other colours on request



Knuckled



Barbed

CHAIN LINK									
Uses	Galvanised			PVC Coated Bright Core			PVC Coated Galvanised Core		
	Height	Mesh	Wire Size	Height	Mesh	Wire Size	Height	Mesh	Wire Size
Garden/domestic Property Borders Temporary Fencing	900mm to 1800mm	50 mm	2.50 mm	900 mm to 1800mm	50mm	2.50/1.70 mm or 3.15/2.24 mm	900mm to 1800mm		3.15/ 2.24mm
Children's Playgrounds Gen. Boundary use Playing fields General usage	1200mm to 1800mm	50mm	2.50mm or 3.55mm	1200mm to 1800mm	50mm	3.15/2.24 mm or 4.00/3.00 mm	1200mm to 1800mm	50mm	3.15/ 2.24mm or 4.00/ 3.00mm
Railway boundaries General purposes	1400mm to 1800mm	40mm	3.00mm				1400mm to 1800mm	40mm	3.55/ 2.50mm
Commercial Properties Industrial Security General purposes	1800mm to 3600mm	50mm	3.00mm or 3.55mm	1800mm to 3600mm	50mm	3.55/2.50 mm or 4.00/3.00 mm	1800mm to 3600mm	50mm	3.55/ 2.50mm or 4.75/ 3.55mm
High security Anti-intruder installations	2400mm to 3600mm	50mm	5.00mm				2400mm to 3600mm	50mm	4.75/ 3.55mm or 6.40/ 4.70mm
Tennis courts	2750mm to 3600mm	50mm or 45mm	2.50mm or 3.00mm	2750mm to 3600mm	50mm or 45mm	3.15/2.24 mm or 3.55/2.50 mm	2750mm to 3600mm	50mm or 45mm	3.15/ 2.24mm or 3.55/ 2.50mm
Driving ranges	2400mm to 3600mm	25mm	2.50mm				2400mm to 3600mm	25mm	2.65/ 1.90mm or 3.15/ 2.24mm

**Applications**

The Chain link system is recommended for the professional fencing of garden and court yards, playgrounds, and sport fields, tennis courts, factories and workshops.

