

GMAX™ II

Petrol-powered Airless Sprayers

“More compact, yet more powerful”



www.graco.be

PROFESSIONAL ADVANTAGES

- Exclusive ProConnect™ pump attachment
- High performance
- Big tip sizes

MATERIALS

Primers - Emulsions - Water based paint - Solvent based paint - Latex - Acrylic

Painter - Heavy Duty Applications

GMAX™ II 3900 - GMAX™ II 5900 - GMAX™ II 7900



GMAX™ II

Petrol-powered airless sprayers
"More compact, yet more powerful"

ACCESSORIES

Gun

241705 TexSpray blue gun with GHD631 and GHD guard

Easy Out™ Pump Filters

244071 30 mesh, grey
 244067 60 mesh, black
 244068 100 mesh, blue
 244069 200 mesh, red

Hoses (230 bar)

240797 3/8" x 15 m
 241274 3/8" x 20 m
 241275 3/8" x 30 m

Whips (230 bar)

238358 3/16" x 0.9 m
 238959 3/16" x 1.4 m
 238359 3/16" x 1.8 m

TexSpray kits = Texture gun, 3/8" hose, whip, GHD 631 tip

241338 230 bar
 244925 280 bar

Pump Lower kits

287512 GMax™ II 3900
 287579 GMax™ II 5900
 249122 GMax™ II 7900

Hopper

241318 90 liter hopper kit
 248531 Bag roller kit
 243428 Wheel kit for hopper

Atomizer Kit

244052 Air atomizer kit with hose

PRO Tip Extensions

with RAC®X Guard
 287019 25 cm
 287020 40 cm
 287021 50 cm
 287022 75 cm

CleanShot™ Pole Gun

287026 90 cm w/ RAC®X
 287027 180 cm w/ RAC®X

Other

233698 Flat spring for improved priming and less cavitation

Tips

GHDXXX GHD tips
 LTXXX RAC®X long life tips
 TMXXX Plaster reversible tips
 WRXXX Wide RAC®X

Guards

222674 GHD guard
 243161 RAC®5 guard
 246125 RAC®X guard

Liquids

206994 TSL™ 0.25l
 243103 Pump Armor™ 1l
 245133 Pump Armor 3.8 l



SmartControl™

WatchDog™ now with toggle on/off switch
 Easy-to-service with flip down access



AutoClean™ 2

Reverse flushes and automatically shuts-off



Flow-through filter

Advantage Drive™ System

Time-tested drive system
 Automatically adjusts and aligns

Endurance™ Pump


Chromex™ rod (3900/5900) long life!
 Durable, solvent resistant drain tubes
 Maxlife™ on GMAX™ II 7900

Pneumatic Tyres

All terrain for all conditions
 Inner tubes



1



Unscrew paint line

2



Open latch that opens front cover

3



Remove pin.
 Pump lower is free.



EXCLUSIVE PUMP ATTACHMENT
 Remove and replace your entire pump lower:
 On the job - without any tools - in seconds

GMAX™ II

SPECIFICATIONS



	GMAX™ II 3900	GMAX™ II 5900	GMAX™ II 7900
Part numbers	249335	248699	249337
Max Tip Size	- 1 gun - 2 guns	0.035" 0.025"	0.043" 0.031" 0.047" 0.035"
Max. Flow	4.7 l/min	8.0 l/min	8.3 l/min
Max. Pressure	230 bar	230 bar	230 bar
Max. Hose Length	45 m	60 m	75 m
Honda® Engine	3.0 kW	4.1 kW	4.8 kW
Engine Displacement	118 cm³	163 cm³	196 cm³
Fuel Tank Capacity	2.5 l	3.6 l	3.6 l
Fuel Consumption	313 g/kW.hr - 230 g/HP.hr	313 g/kW.hr - 230 g/HP.hr	313 g/kW.hr - 230 g/HP.hr
Weight	50 kg	64 kg	67 kg

GMAX™ II 3900 and II 7900:

ship complete and ready to spray. Include 15m x 3/8" BlueMax™ Hose, and 90 cm Whip Hose and Swivel for comfort spraying as well as the blue Texture gun mounted with RACX™531 Tip and Guard. An Accessory Box is added for convenient storage of Tools, Tips, TSL™ bottle and other Accessories.

II GMAX™ II 5900:

ships the same as above, but does not include AutoClean™ 2 Valve and does not include the Accessory Box.