

max clear span for pedestrian loadings (mm)	def (mm)	L.B.B. size (mm)	'N' load bars at 30mm centres													Self Colour Weights per square metre (kgs)	Binding Bar Weight (based on 2 x 1m) (kgs)			
			clear span (mm)																	
			300	450	600	750	900	1050	1200	1350	1500	1650	1800	1950	2100					
a.1050	3.41	20 x 3	kN/m ²	108	48.0	24.7	12.6	7.3											17.58	0.86
b.1020	5.06		D (mm)	0.82	1.84	2.99	3.72	4.47												
c. 890	4.40																			
a.1450	6.34	25 x 3	kN/m ²	169	75.0	42.0	24.7	14.3	9.01	6.05	4.24								21.02	1.08
b.1275	6.32		D (mm)	0.65	1.47	2.60	3.74	4.49	5.25	6.00	6.75									
c.1110	5.45																			
a.1815	9.01	30 x 3	kN/m ²	243	108	60.7	38.5	24.7	15.6	10.5	7.34	5.35	4.02						24.76	1.30
b.1535	7.68		D (mm)	0.54	1.23	2.18	3.37	4.50	5.25	6.00	6.75	7.50	8.25							
c.1340	6.69																			
a.1980	9.90	35 x 3	kN/m ²	332	147	82.9	53.0	36.7	24.8	16.6	11.7	8.50	6.38	4.91	3.86				28.16	1.50
b.1790	8.95		D (mm)	0.47	1.05	1.87	2.92	4.20	5.25	6.00	6.75	7.50	8.25	9.00	9.75					
c.1560	7.74																			
a.2190	10.0	40 x 3	kN/m ²	434	193	108	69.0	48.0	35.0	24.8	17.4	12.7	9.53	7.34	5.77	4.40			31.90	1.72
b.2030	9.91		D (mm)	0.41	0.92	1.63	2.55	3.68	4.97	6.00	6.75	7.50	8.25	9.00	9.75	10.0				
c.1780	8.79																			

max clear span for pedestrian loadings (mm)	def (mm)	L.B.B. size (mm)	'N' load bars at 30mm centres													Self Colour Weights per square metre (kgs)	Binding Bar Weight (based on 2 x 1m) (kgs)			
			clear span (mm)																	
			300	450	600	750	900	1050	1200	1350	1500	1650	1800	1950	2100					
a.1350	5.58	20 x 5	kN/m ²	181	80.0	41.3	21.1	12.2	7.70	5.10									28.16	1.50
b.1210	6.01		D (mm)	0.82	1.84	3.00	3.75	4.49	5.25	6.00										
c.1055	5.21																			
a.1790	8.84	25 x 5	kN/m ²	282	125	70.0	41.2	23.9	15.1	10.1	7.08	5.16	3.88						34.32	1.86
b.1510	7.46		D (mm)	0.66	1.47	2.60	3.74	4.50	5.25	6.00	6.75	7.50	8.25							
c.1320	6.53																			
a.2010	10.0	30 x 5	kN/m ²	405	180	101	64.5	41.3	26.0	17.4	12.2	8.92	6.70	5.16	4.60				40.74	2.24
b.1815	9.01		D (mm)	0.54	1.23	2.17	3.39	4.50	5.25	6.00	6.75	7.50	8.25	9.00	9.75					
c.1580	7.76																			
a.2260	10.0	35 x 5	kN/m ²	554	246	138	88.3	61.2	41.3	27.7	19.4	14.2	10.6	8.19	6.44	4.91			46.86	2.60
b.2090	10.0		D (mm)	0.47	1.05	1.87	2.92	4.20	5.25	6.00	6.75	7.50	8.25	9.00	9.75	10.0				
c.1850	9.19																			
a.2520	10.0	40 x 5	kN/m ²	722	311	180	115	80.0	58.6	41.3	29.0	21.1	15.9	12.2	9.62	7.33			53.32	2.98
b.2310	10.0		D (mm)	0.41	0.89	1.63	2.55	3.68	4.99	6.00	6.75	7.50	8.25	9.00	9.75	10.0				
c.2080	9.83																			
a.2790	10.0	45 x 5	kN/m ²	917	405	228	146	101	74.0	55.0	41.3	30.1	22.6	17.4	13.7	10.5			59.78	3.36
b.2525	10.0		D (mm)	0.37	0.82	1.45	2.27	3.26	4.43	5.61	6.75	7.50	8.25	9.00	9.75	10.0				
c.2280	10.0																			
a.3050	10.0	50 x 5	kN/m ²	1130	503	282	180	125	91.0	70.0	55.2	41.2	31.0	23.9	18.8	14.3			65.90	3.72
b.2730	10.0		D (mm)	0.33	0.74	1.31	2.04	2.94	3.97	5.21	6.58	7.50	8.25	9.00	9.75	10.0				
c.2460	10.0																			
a.3550	10.0	60 x 5	kN/m ²	1630	718	407	260	180	132	101	79.5	64.4	53.1	41.3	32.5	24.8			78.82	4.48
b.3130	10.0		D (mm)	0.27	0.61	1.09	1.71	2.46	3.34	4.35	5.48	6.77	8.17	9.00	9.75	10.0				
c.2830	10.0																			

Safe uniformly distributed loads (U.D.L.) in kilonewtons per square metre on simply supported panels with deflections (δ) in mm. Based on a working stress of 180 N/mm². Loads shown in the white area have been reduced to keep the deflections within 1/200th of the clear span or 10mm whichever is the lesser.

- a** – Light Duty 3 kN/m² described as access limited to one person only
- b** – General Duty 5 kN/m² described as regular two way pedestrian traffic
- c** – Heavy Duty 7.5 kN/m² described as high density pedestrian traffic

Load Table Designs allow for a 1kN load over a 300mm x 300mm area in accordance with BS 4592-0:2006
Weights shown are for transverse bars at 100mm centres. For 50mm centres add 2.4kg per M²