



FOUNDATIONS
 The foundation sizes indicated are for 'normal' ground conditions only, and may require modification to suit the prevailing ground conditions on site. The concrete foundations should not be leaner by mass than 1 part Cement to 10 parts of 20mm nominal graded aggregates, and must be thoroughly compacted prior to the initial set.

POSTS
 Intermediate posts are 120x60 section RHS holed and inserted in the front & rear face with M8 threaded inserts.
 Corner posts are 120x60mm section SHS holed and inserted in the front and side face with M8 threaded inserts.

PANELS
 The standard panel configurations available for the system are:
 3.0m High Nylofor Rebound panel & 2.0m High Nylofor 2D Super panel & 1.0m High Nylofor 2D Super panel, or
 3.0m High Nylofor Rebound panel & 2.0m High Nylofor Make Up panel & 1.0m High Nylofor Make Up panel

FIXINGS
 There are two fixing options available for the Bekasport system:
 OPTION 1 : Nylofor Fixing Brackets securing the full Height of the panel.
 OPTION 2 : Betafence U-Profile Clamp bar securing lower 2.0m & Nylofor Fixing Brackets at the top.

FENCE HEIGHT	POST LENGTH	POST SECTIONS	FOUNDATION DEPTH			
6.0m	6900mm	120x60x3mm & 120x60x3mm	750mm			
PANEL COMBINATIONS			FIXING OPTIONS (Double on Corner)			
OPTION 1		OPTION 2		OPTION 1		OPTION 2
3.0m Nylofor Rebound & 2.0m N2DSuper & 1.0m N2D Super		2.0m Nylofor Rebound & 2.0m Make Up & 1.0m Make Up		16no. Nylofor Fixing Brackets		1no. U-Profile Clamp Bar & 10no. Nylofor Fixing Brackets

Revision

RIDGEFENCE
 info@ridgeway-online.com
 www.ridgeway-online.com

Ridgeway
 103 Airport Road West
 Belfast BT3 9ED
 Tel 02890 454599
 Fax 02890 44596

Betafence Ltd. reserves the right to amend & withdraw products detailed herein without prior notice.
 COPYRIGHT © 2010
 BETAFENCE LTD -
 SHEFFIELD - ENGLAND

SPORTS REBOUND 6.0M HIGH

Drawn	SB	Date	12-08-10
Drawing No.			REV
BEKASPORT-PLUS-60			