



Panels

Securifor is the ultimate in discreet high security perimeter protection. These systems combine an anti-climb and anti-cut fence with excellent through visibility.



Applications

The Securifor system is developed for all applications where total security is essential: schools, warehouses, distribution centres, power plants, laboratories, computer centres, financial institutions, military sites, penitentiaries, etc. For specific applications (e.g. prisons) particular solutions can be proposed.

Securifor[®] 358 / Super 6

Benefits

Vandal resistant

The finger-proof aperture combined with 4mm wire diameter provides a substantial barrier that is difficult to climb and penetrate. Almost impossible to cut wires by use of conventional bolt or wire cutters.

Secure and discreet

The ultimate system for providing a high degree of security where a discreet visual impact on the immediate environment is essential.

Formidable

An effective deterrent to intruders available in various heights up to 6m - specially designed for high security applications. Compatible with electronic alarm and detection systems.

6mm Vertical wires

Securifor Super 6 is the highest level of security panel within the Securifor range. This NEW panel incorporates 6mm vertical wires to give maximum resistance to cut through attacks.

Through visibility

The system has excellent see-through visibility particularly important for camera surveillance.

Available as a complete system

The system consists of panels in various heights, square posts with a specific fixing system and a wide assortment of innovative swing and sliding gates.



Panels

The panels are 2515 mm wide and heights range from 900 to 5200 mm. Mesh sizes are 76.2 x 12.7 mm, and manufactured from 4mm wires (**Securifor Super 6 has 6mm vertical wires**). Weld strength is 75% of the minimum tensile strength of the wire (tensile range 540-690 N/m²).

Featuring a toe and finger proof mesh aperture, this system combines an anti-climb and anti-cut fence with excellent through visibility and resistance to vandalism.

Extra length panels can be supplied (+300 mm) for below ground to prevent burrowing.



Secured by Design

Securifor 358 / Super 6 is a secured by design product. Having passed the standards and tests which are required to achieve Police Preferred Specification.

Posts and fixings

Securifor Posts

Securifor posts are manufactured from 60x60mm and 80x80mm square hollow section and are holed for bolt through fixing. Posts come inclusive of top caps.

Panels are fixed using 25 x 5mm slotted clamp bar, M8 x 100 galvanised cup square round bolts and sheer-nuts, fixings at 305mm centres.



Post system Bekasecure

The Bekasecure post's design and high yield strength steel provide the ultimate in high security, rigidity and ease of installation. Posts are foreseen with a double range of wholes 10 x 20 mm and the fixation of the panels is secured by the use of a continuous cover plate and specific inox

security bolts. The open profile of the post allows electrical or fibre optic cabling and is closed with specific metal cap.

- Post profile
- 140 x 119 x 3,00 mm (h. fence 3 - 4 m)
- 140 x 150 x 5,00 mm (h. fence 4,2 - 6 m)

Security

Securifor 358 / Super 6 satisfy the requirements for Category: 2 (Security), Category: 3 (High Security) and Category: 4 (Maximum Security) fences.

Gates

The Securifor system can be supplied complete with Securifor or Robusta swing and/or sliding gates for optimal protection.

Coating

Panels are manufactured from pre-galvanised wires. An adhesion coating is applied to allow perfect adhesion with the polyester coating (min. 100 micron). Posts are polyester coated with a galvanised substrate in accordance with Euro norm 10147.

All Betafence powder coated products are tested for adherence to 1000 hour Salt Spray testing according to DIN 50021 (= ASTM B 117 = ISO 9227) + DIN 53167 and conforming to EN 10223 - 7.

The panels are also available coated in Zinalu Super (95% zinc, 5% aluminium): on request.

Colours

Standard colours are Green RAL6005 and Black RAL9005.

Other colours available on request.

ASSORTMENT SECURIFOR 358 / SUPER 6

Panels			Posts				
Fence height mm	Height x Width mm	Number of beams per panel	Section mm	Overall length mm	Intermediate	Corner	End
					-	-	-
1270	1270 x 2515	0 (flat panel)	-	-	-	-	-
2400	2400 x 2515	0 (flat panel)	60 x 60 x 2.5	3100	9	18	9
2700	2700 x 2515	0 (flat panel)	80 x 80 x 2.5	3400	10	20	10
3000	3000 x 2515	0 (flat panel)	80 x 80 x 2.5	3800	11	22	11
3300	3300 x 2515	0 (flat panel)	Specifications available on request				
3600	3600 x 2515	0 (flat panel)					
4000	4000 x 2515	0 (flat panel)					
4500	4500 x 2515	0 (flat panel)					
4800	4800 x 2515	0 (flat panel)					
5200	5200 x 2515	0 (flat panel)					

Comprehensive installation documents are available by request to our sales office.

