



Panels

Bekasport is the ideal system to fence and protect all types of sports and recreational areas.

Bekasport® / Ridgefence Sports Standard

Benefits

Maximum rigidity

The use of the Nylofor 2D panel gives this system extremely high level of rigidity.

Heights up to 6m

The Bekasport system is available for ball-stop heights up to 6m.

Varimesh panel

The 'varimesh' panel is designed with mixed mesh apertures the lower third having a high density mesh for maximum strength in the contact area.

Sound damping fixings

Specific sound damping fixings are used in this system which greatly reduces the noise generated by impact on the fence.

Wide choice of colour options

An extensive range of standard and non standard colour options can be made available.

Available as a complete system


The system consists of various heights and all components have been developed to provide a professional product of high quality that can be installed efficiently and rapidly.

Applications

The Betafence unique ball-stop system is an ideal solution for fencing sport or playgrounds. The system is a combination of a special post with panels type Nylofor 2D.



Panels



The panels are manufactured from heavy welded mesh, 2500mm wide and heights range from 3000 to 6000mm and are constructed from a unique 'varimesh' pattern to provide a lower rebound area 1200mm high.

The panels are extremely rigid and secure due to the double horizontal wires one positioned on either side of the verticals. This system is ideally suited to a games containment area, with provision for recessed goal areas and increased heights across goal ends or goal areas.

Posts

The rectangular posts are equipped with plastic sound damping clips. Thanks to a special insert in the posts these clips are located within the post. This means that the clip is an installation aid for hanging the panels. After hanging, the panel is fixed to the Bekasport post by means of steel clips.

Gates

The Bekasport system can be supplied complete with Nylofor or Robusta swing gates.

Coating

Panels are manufactured from pre-galvanised wires. An adhesion coating is applied to allow perfect adhesion with the polyester coating (min. 100 micron). Posts are polyester coated with a galvanised substrate in accordance with Euro norm 10147.

All Betafence powder coated products are tested for adherence to 1000 hour Salt Spray testing according to DIN 50021 (= ASTM B 117 = ISO 9227) + DIN 53167 and conforming to EN 10223 - 7.

Colours

Standard colours are Green RAL6005.

Other colours available on request.

ASSORTMENT BEKASPORT

Panels			Posts		
Fence height mm	Lower panel Width x Height mm	Upper panel Width x Height mm	Section mm	Overall length mm	Number of fixings
3000	3030 x 2500	–	70 x 50 x 2	3800	10
4000	3030 x 2500	1030 x 2500	80 x 50 x 3	4800	12
5000	3030 x 2500	2030 x 2500	120 x 50 x 4	6000	16
6000	3030 x 2500	2030 + 1030 x 2500	120 x 50 x 4	7000	18

Comprehensive installation documents are available by request to our sales office.

