



Rolls

The Sentinel Chain Link system is a fencing system that is versatile and easy to install.

Sentinel® Chain Link

Benefits

Versatile

A well proven popular, versatile and easy to erect fencing suitable for a wide variety of applications.

Long lifetime

The coating technology of Betafence is state of the art and guarantees an extra high longevity. After galvanising the wire can be given an extra protection coating of durable PVC.

Easy to use

A professional product of high quality that is easy to use and can be installed efficiently and rapidly.

Applications

The Sentinel Chain Link system is recommended for the professional fencing of garden and court yards, playgrounds, and sport fields, tennis courts, factories and workshops.



Mesh

A well proven popular, versatile and easy to erect fencing suitable for a wide variety of applications. From a simple boundary marker to a permanent secure fence, there will be a specification of Chain Link suited to the purpose.

Most Chain Link is available compact wound and palletised. Standard PVC colours are green or black.

Available in either barbed or knuckled edges or combination of both.

Supplied standard in 12.5 m rolls



Knuckled Top



Barbed Top

Security

Sentinel Chain Link satisfies the requirements for Category: 1 (General Purpose) and Category: 2 (Security) fences.

Gates

The system can be supplied complete with Nylofor or Robusta swing and/or sliding gates for optimal protection.

Colour

Standard PVC colours are green or black.

Coating

Galvanised.

PVC coated bright core.

PVC coated galvanised core.

ASSORTMENT SENTINEL CHAIN LINK

| Rolls | | | Rolls | | | Rolls | | |
|-------------------|-------------------|----------------|------------------------|-------------------|----------------|----------------------------|-------------------|----------------|
| Fence height mm | Height x Length m | Mesh x Wire mm | Fence height mm | Height x Length m | Mesh x Wire mm | Fence height mm | Height x Length m | Mesh x Wire mm |
| GALVANISED | | | PVC BRIGHT CORE | | | PVC GALVANISED CORE | | |
| 900 | 0.9 x 25 | 50 x 2.5 | 900 | 0.9 x 25 | 50 x 2.5/1.7 | 900 | 0.9 x 25 | 50 x 3.15/2.24 |
| 1200 | 1.2 x 25 | 50 x 2.5 | 1200 | 1.2 x 25 | 50 x 2.5/1.7 | 1200 | 1.2 x 25 | 50 x 3.15/2.24 |
| 1400 | 1.4 x 25 | 50 x 2.5 | 1400 | 1.4 x 25 | 50 x 2.5/1.7 | 1800 | 1.8 x 25 | 50 x 3.15/2.24 |
| 1800 | 1.8 x 25 | 50 x 2.5 | 1800 | 1.8 x 25 | 50 x 2.5/1.7 | 2400 | 2.4 x 25 | 50 x 3.15/2.24 |
| 2400 | 2.4 x 25 | 50 x 2.5 | 900 | 0.9 x 25 | 50 x 3.15/2.24 | 2750 | 2.75 x 25 | 50 x 3.15/2.24 |
| 900 | 0.9 x 25 | 50 x 3 | 1200 | 1.2 x 25 | 50 x 3.15/2.24 | 3600 | 3.6 x 25 | 50 x 3.15/2.24 |
| 1200 | 1.2 x 25 | 50 x 3 | 1400 | 1.4 x 25 | 50 x 3.15/2.24 | 900 | 0.9 x 25 | 50 x 3.55/2.5 |
| 1400 | 1.4 x 25 | 50 x 3 | 1500 | 1.5 x 25 | 50 x 3.15/2.24 | 1200 | 1.2 x 25 | 50 x 3.55/2.5 |
| 1500 | 1.5 x 25 | 50 x 3 | 1800 | 1.8 x 25 | 50 x 3.15/2.24 | 1800 | 1.8 x 25 | 50 x 3.55/2.5 |
| 1800 | 1.8 x 25 | 50 x 3 | 2400 | 2.4 x 25 | 50 x 3.15/2.24 | 2400 | 2.4 x 12.5 | 50 x 3.55/2.5 |
| 2150 | 2.4 x 12.5 | 50 x 3 | 2750 | 2.75 x 12.5 | 50 x 3.15/2.24 | 2750 | 2.75 x 12.5 | 50 x 3.55/2.5 |
| 2400 | 2.4 x 12.5 | 50 x 3 | 3050 | 3.05 x 12.5 | 50 x 3.15/2.24 | 3600 | 3.6 x 12.5 | 50 x 3.55/2.5 |
| 2750 | 2.75 x 12.5 | 50 x 3 | 900 | 0.9 x 25 | 50 x 3.55/2.5 | 1800 | 1.8 x 12.5 | 50 x 4/3 |
| 3600 | 3.6 x 12.5 | 50 x 3 | 1200 | 1.2 x 25 | 50 x 3.55/2.5 | 2400 | 2.4 x 12.5 | 50 x 4/3 |
| 1800 | 1.8 x 12.5 | 50 x 3.55 | 1800 | 1.8 x 25 | 50 x 3.55/2.5 | 2750 | 2.75 x 12.5 | 50 x 4/3 |
| 2400 | 2.4 x 12.5 | 50 x 3.55 | 2150 | 2.15 x 12.5 | 50 x 3.55/2.5 | 1800 | 1.8 x 12.5 | 50 x 4.75/3.55 |
| 2750 | 2.75 x 12.5 | 50 x 3.55 | 1800 | 1.8 x 12.5 | 50 x 4/3 | 2150 | 2.15 x 12.5 | 50 x 4.75/3.55 |
| | | | | | | 2400 | 2.4 x 12.5 | 50 x 4.75/3.55 |
| | | | | | | 2750 | 2.75 x 12.5 | 50 x 4.75/3.55 |

