



## Rolls

**Manufactured from high tensile wire – over twice the strength of traditional Chain Link fencing.**

## Sentinel<sup>®</sup> Super 70

### Benefits

---

#### High security

Sentinel Super 70 provides a chain link fence with a significantly higher degree of security and performance against 'cut through'. Manufactured throughout from High Tensile wire – over twice the strength of traditional Chain Link. The increase strength of the wire allows for greater tensioning making the fence difficult to vandalise and dismantle.

#### High longevity

Betafence's state of the art coating technology provides Super 70 with increased resistance to corrosion. Wires are heavily galvanised prior to a unique green treatment.

#### Rigidity and strength

A rigid fence with increased strength is, achieved as a result of using high tensile wires.

#### Professional installation

Developed to provide a professional product of high quality that can be installed efficiently and rapidly.

## Applications

Sentinel Super 70 is designed for applications where an increased level of strength and security is required: Highways, Track side, Military, Airports, Power plants and sports stadium.



**Mesh**

Provides increased levels of security compared to traditional Chain Link Fencing.

Manufactured from High Tensile wire 70tpsi (1050 N/mm<sup>2</sup>)

Mesh and wire:

40 mm x 3 mm

50 mm x 3 mm or 3.55 mm

**Presentation**

Supplied standard in 12.5 m rolls

Barbed or Knuckled edges or a combination of both are available



Knuckled Top



Barbed Top

**Security**

Sentinel Super 70 satisfies the requirements for Category: 1 (General Purpose) and Category: 2 (Security) fences.

**Gates**

Sentinel Super 70 can be supplied complete with Nylofor or Robusta swing and/or sliding gates for optimal protection.

**Coating**

Wires are heavily galvanised prior to a unique green treatment to provide increased resistance to corrosion.

**Colours**

Green.

**ASSORTMENT SENTINEL SUPER 70**

Wire Size mm	Height mm							
	900	1200	1400	1800	2000	2400	2750	3600
3.00	•	•	•	•	•	•	•	•
3.55	•	•	•	•	•	•	•	•

Comprehensive installation documents are available by request to our sales office.

