

Products, training and operational support services for professional work at height and rescue

## Piranha adjustable l'yrd - 2m no connectors

LA02

Used to provide support when in a working position and for work restraint.

Adjustable lanyard to allow precise positioning for the work task.

- Range of lengths and connector options
- Protective sleeve
- Adhesive heat shrink
- One hand operation
- Easy to use even when wearing gloves
- User replaceable rope

Protection sleeve protects against abrasion, sharp edges and contamination.

The use of screwlinks (certain models) helps eliminate the risk of side or cross loads, and can be a semi-permanent attachment if required.

Adhesive heat shrink prevents the ID label from being damaged or lost. Replacement ropes available. Can be fitted by the user in minutes and requires only a screwdriver.

User can always maintain a grip of the structure for support when adjusting. When used for positioning an additional fall protection system should be used.

Meets the requirements of EN795 type B

Code	Length	Anchorage connector	Harness connector
LA02	2m	none	none
LA02H	2m	safety hook	screwlink
LA02T	2m	twistlock	triact*
LA03	3m	none	none
LA03H	3m	safety hook	screwlink
LA03T	3m	twistlock	triact
LA05	5m	none	none
LA05H	5m	safety hook	screwlink
LA05T	5m	twistlock	triact
LA10	10m	none	none
LA20	20m	none	none

\* complies with Siemens PPE requirements PRO-13838 Ap1



### Specifications:

**Size:**

**Materials:** Alloy & stainless steel rope device, polyamide rope lanyard,

**EN test Mass:** 125kg

**Loading:**

**Weight (kg):**

**Conformity:** EN358

**Markets:** Roof safety, wind turbine climbers, telecoms and pylon climbing, fire and rescue service, USAR.

*Specifications may change without notice.*